## Automatic Wire Polishing Machine MODEL: WPA 15, 25 & 35





These machines are designed and developed for resizing and repolishing of the bearing length of Polycrystalline, Natural and Mono Diamond dies.

The Machine is manufactured with precision engineering and especially consists of self centering type oscillating die holder and reciprocating wire clamping device. Die rotation and stroke speeds are continuously variable. Individual controls are provided for die rotation, stroke and oscillation. All operations are controlled by electronic timer with digital display. Spindle and stroke motors are controlled through AC drives. The model WPA2S & 3S is having same features as WPA1S but with independently controlled spindles. The machine is supplied with a set of spares and standard accessories which makes a package and ready to use.

## For best results always use Mikrotek Diamond powders

- \*Hand wire puller can be supplied as an optional accessory.
- \*WPAB1S model is used for die sizes up to 10 mm.

Specification are subject to change without prior notice.

Stroke length         75 mm           Die size range         0.010 -           Die speed         0 - 300           Stroke speed         0 - 400           Die oscillation         0 - 40°           Case Dia         25 & 28           Case Hight         6 to           Timer         1 sec -	double strokes/min
Die size range $0.010-$ Die speed $0-300$ Stroke speed $0-400$ Die oscillation $0-400$ Case Dia $25 \& 28$ Case Hight $6$ toTimer $1 \sec -$	0 rpm double strokes/min
$\begin{array}{ccc} \text{Die speed} & 0-300 \\ \text{Stroke speed} & 0-400 \\ \text{Die oscillation} & 0-40^{\circ} \\ \text{Case Dia} & 25 \& 28 \\ \text{Case Hight} & 6 \text{ to} \\ \text{Timer} & 1 \text{ sec} - \\ \end{array}$	0 rpm double strokes/min
Stroke speed         0 - 400           Die oscillation         0 - 40°           Case Dia         25 & 28           Case Hight         6 to           Timer         1 sec -	double strokes/min
Die oscillation 0 - 40° Case Dia 25 & 28 Case Hight 6 to Timer 1 sec -	
Case Dia         25 & 26           Case Hight         6 to           Timer         1 sec -	
Case Hight 6 to Timer 1 sec -	(20° each side)
Timer 1 sec –	mm
	mm
Innut voltage 220 Vol	59 hrs
input voitage 220 voi	ts, 50 Hz, 1 phase
M/c Dimensions – 1S 19 X 21	X 28 Inches
M/c Dimensions – 2S 36 X 21	X 28 Inches
M/c Dimensions – 3S 53 X 21	X28 Inches
Net weight 85/150	
Gross weight 145/23	)/274

**Standard accessories:** Mains chord -1no, Container for Diamond paste-7nos, Olive oil-100ml, Round Belt- Dia 6X600mm-1no, Timer Belt 220XL-1no, M6 knob — 4 no's, Latch Switch 24V,DC-1no, Pot Meters — 2 no's, Fuses- 5 Amps-5nos, oil Can



## MIKROTEK MACHINES LIMITED

16, 2nd Cross, 'A' Sector, Amruthnagar Main Road, Karnataka State, Bengaluru - 560 092, India Tel: 91-80-42688999 (30 lines) Email: info@mikrotek.org Web: www.mikrotek.in